



HX 7500 T

PORTABLE POWER

Generating Sets Range INTENS

PRODUCT ADVANTAGES

- Entire group guaranteed 3 years
- HONDA Professional Engine
- Solid and high-performance equipment

Range INTENS

Equipment that is robust, long-lasting and simple to use for repetitive operations in difficult conditions.



HX 7500 T

GENERAL SPECIFICATIONS

| | |
|--|-------------|
| Range | INTENS |
| Frequency (Hz) | 50 Hz |
| Max power (kW) * | 5.70 |
| Max power (kVA) | 7.10 |
| Nominal voltage (V) | 400 |
| Number of Phase | Three phase |
| Fuel | Petrol |
| Tank (L) | 6.10 |
| 75% cons. (l/h) * | 2.50 |
| 75% Autonomy (h) * | 2.40 |
| Sound power level guaranteed LwA dB(A) | 97 |
| Acoustic pressure level @1m in dB(A) | 83 |
| Acoustic pressure level @7m in dB(A) | 69 |

ENGINE SPECIFICATIONS

| | |
|---|---------|
| Engine brand | HONDA |
| Engine ref. | GX390 |
| Distribution | O.H.V. |
| Start | Starter |
| Oil shutdown | Oui |
| Displacement (cm ³) | 389 |
| Oil system capacity including filters (L) | 1.10 |

ALTERNATOR SPECIFICATIONS

| | |
|--------------------------|------------------|
| Technology | Collar and brush |
| AVR Regulation | No |
| Indication of protection | IP 23 |
| Insulation class | H |

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker

DIMENSIONS AND WEIGHT

| | |
|-----------------|----|
| Length (cm) | 77 |
| Width (cm) | 57 |
| Height (cm) | 59 |
| Dry Weight (kg) | 80 |

PACKAGING

| | |
|------------------------------------|--------|
| Packaging type | Box |
| Length (cm) | 78.50 |
| Width (cm) | 58 |
| Height (cm) | 59.50 |
| Weight (kg) | 82.50 |
| Pallet type | 120/80 |
| Number of box by pallet | 6 |
| Pallet height (cm) | 192 |
| weight of the packaged Pallet (kg) | 505 |

ACCESSORIES SUPPLIED




Funnel



User and maintenance manual

OPTIONS



R03

This set includes the hour meter and the differential circuit breaker.



RKB2

Trolley kit for the generating sets superior to 6kW



R19

Maintenance kit for Honda GX390 engines (except Alizé 6000E and Alizé 7500 TE)



RH1

Cover for SDMO 's generating sets, welding sets and water pumps



RPM

Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V